



Executable: wave_f
Resources: 24 processes, 1 node
Machine: mic3
Start time: Thu Oct 31 12:45:06 2013
Total time: 30 seconds (1 minute)
Full path: /home/mark/allinea/perf-report/examples
Notes: 1226400 iterations in 30 seconds



Summary: wave_f is CPU-bound in this configuration

The total wallclock time was spent as follows:



This application run was **CPU-bound**. A breakdown of this time and advice for investigating further is in the **CPU** section below.

CPU

A breakdown of how the 67.6% total CPU time was spent:



The per-core performance is **memory-bound**. Use a profiler to identify time-consuming loops and check their cache performance.

No time was spent in **vectorized instructions**. Check the compiler's vectorization advice to see why key loops could not be vectorized.

I/O


A breakdown of how the 0.0% total I/O time was spent:



No time is spent in **I/O operations**. There's nothing to optimize here!

MPI


Of the 32.4% total time spent in MPI calls:



The **point-to-point** transfer rate is low. This can be caused by inefficient message sizes, such as many small messages, or by imbalanced workloads causing processes to wait. Use an MPI profiler to identify the problematic calls and ranks.

Memory

Per-process memory usage may also affect scaling:



The **peak node memory usage** is low. You may be able to reduce the total number of CPU hours used by running with fewer MPI processes and more data on each process.